EDGEWATER CONDOMINIUMS OF BROWARD EWC - BUILDING 11 8801 WILES ROAD CORAL SPRINGS, FLORIDA



FLORIDA TECHNICAL, INC.

114 WEST DAVIS BLVD

TAMPA, FLORIDA 33606

813-765-0264 * 813-699-8323 (FAX)

THOMAS.FLTECH@GMAIL.COM

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: Aug 25, 2022							
Owner Information							
	Name: EDGEWATER COND	OMINIUM - EWC 11	NIUM - EWC 11		Contact Person: E. HERRON Home Phone:		
	8801 WILES ROAD				2004		
	CORAL SPRINGS	Zip: 33067		Work Phone: 954-344	-3601		
	BROWARD			Cell Phone:			
	e Company:	1		Policy #:			
Year of 1	Home: 1986	# of Stories: 3		Email:			
accomp	Any documentation used in vany this form. At least one plot. The insurer may ask addit	otograph must accompa	ny this form to validate	e each attribute marked			
the H	ding Code: Was the structure by IVHZ (Miami-Dade or Browar A. Built in compliance with the a date after 3/1/2002: Building B. For the HVHZ Only: Built in provide a permit application with C. Unknown or does not meet to a Covering: Select all roof covering of Original Installation/Re	d counties), South Florida FBC: Year Built Permit Application Date (was a compliance with the SFB th a date after 9/1/1994: Buther requirements of Answerering types in use. Provide	Building Code (SFBC-9 For homes built in a MMDD/YYYY) / / C-94: Year Built uilding Permit Application r "A" or "B" the permit application d	4)? 2002/2003 provide a perm For homes built in 199 on Date (MM/DD/YYYY)/ ate OR FBC/MDC Produc	out application with 94, 1995, and 1996 / ct Approval number		
	ring identified.	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
		Date	Troutet Approvar#	керіасешені	Сотриансе		
	Asphalt/Fiberglass Shingle		EL 7004 D7	0040			
	2. Concrete/Clay Tile	03/,19/,13	FL7804-R7	2013	Ц		
	3. Metal				Ш		
	4. Built Up						
	5. Membrane						
	6. Other						
3. Roof	A. All roof coverings listed about a stallation OR have a roofing part application after C. One or more roof coverings meet the roof coverings meet th	permit application date on a ami-Dade Product Approv 9/1/1994 and before 3/1/2 do not meet the requirement equirements of Answer "A e weakest form of roof decard (OSB) roof sheathing at 6" along the edge and 12 crews, nails, adhesives, other of the options B or C belong with a minimum thickness paced a maximum of truss/rafter spacing that is field or has a mean uplift g with a minimum thickness gwith a minimum thickness grant of the options are a maximum of the options and the options are a maximum of th	or after 3/1/02 OR the roval listing current at time 002 OR the roof is originate of Answer "A" or "B". "" or "B". "" attached to the roof truss 2" in the fieldOR- Bather deck fastening system ow. "" os of 7/16" inch attached shown to have an equivaresistance of at least 103 ares of 7/16" inch attached sess of 7/16" inch attached	of is original and built in of installation OR (for the nal and built in 1997 or law). //rafter (spaced a maximum ten decking supporting we nor truss/rafter spacing the law). I to the roof truss/rafter (spaced and or greater resistance psf.	2004 or later. e HVHZ only) a ter. m of 24" inches o.c.) rood shakes or wood hat has an equivalent paced a maximum of tws, nails, adhesives, than 8d nails spaced paced a maximum of		
(24"inches o.c.) by 8d common decking with a minimum of 2 nors Initials TEC Property Advised Property Property Advised Property Property Advised Property Property Property Advised Property Pro	ails per board (or 1 nail pe	r board if each board is		nes in width)OR-		

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

Ins	spect	tors	Initials	EC Property Address 8801 WILES ROAD	CORAL SPRINGS	33067
		<u>B.</u> <u>C.</u>	No SWR. Unknown	or undetermined.		
	Sec	<u>A.</u>	SWR (also	Resistance (SWR): (standard underlayments or hot-mopped felts do not quality called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing up for foam adhesive SWR barrier (not foamed-on insulation) applied as a supplem	nderlayment applied directly	to the
	X	C.	Other Roof	less than 2:12. Roof area with slope less than 2:12 sq ft; Total 1 Any roof that does not qualify as either (A) or (B) above.	roof areasq ft	
			Flat Roof	Total length of non-hip features: feet; Total roof system perimeter Roof on a building with 5 or more units where at least 90% of the main ro	r: feet of area has a roof slope of	
	the		structure of Hip Roof	over unenclosed space in the determination of roof perimeter or roof area for ro Hip roof with no other roof shapes greater than 10% of the total roof syste		
5.	Ro	of G	eometry: V	What is the roof shape? (Do not consider roofs of porches or carports that are at		
	H		No attic ac	or unidentified coess		
	Ħ	F.	Other:			
	П	E.	Structural	both sides, and is secured to the top plate with a minimum of three nails on each Anchor bolts structurally connected or reinforced concrete roof.	ch side.	
				a minimum of 2 nails on the front side, and a minimum of 1 nail on the oppose Metal connectors consisting of a single strap that wraps over the top of the trust	ss/rafter, is secured to the w	all on
				Metal Connectors consisting of 2 separate straps that are attached to the wall fabeam, on either side of the truss/rafter where each strap wraps over the top of the strap wraps over the top of the truss/rafter where each strap wraps over the top of the strap wraps over the strap wr	the truss/rafter and is secure	
		D.	Double W		, 	
	ت	~• '		Metal connectors consisting of a single strap that wraps over the top of the minimum of 2 nails on the front side and a minimum of 1 nail on the opposing		with a
	∇	C	Single Wra	position requirements of C or D, but is secured with a minimum of 3 nails.	and does not meet t	
			님	Metal connectors that do not wrap over the top of the truss/rafter, or Metal connectors with a minimum of 1 strap that wraps over the top of the trus	ss/rafter and does not meet t	he nail
		<u>B.</u>	Clips			
			X	Attached to the wall top plate of the wall framing, or embedded in the bond be the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, a corrosion.		from
	IVIII	uma		ns to qualify for categories B, C, or D. All visible metal connectors are: Secured to truss/rafter with a minimum of three (3) nails, and		
	1 / f :	 -	الله	Metal connectors that do not meet the minimal conditions or requirements of B	3, C, or D	
				Truss/rafter anchored to top plate of wall using nails driven at an angle through the top plate of the wall, or		ed to
			Toe Nails	of outside corner of the roof in determination of weakest type)		
4.				ichment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include att or outside corner of the roof in determination of WEAKEST type)	achment of hip/valley jacks	within
			No attic ac			
	H			or unidentified.		
				l Concrete Roof Deck.		
		•	greater resi 2 psf.	stance than 8d common nails spaced a maximum of 6 inches in the field or has	s a mean uplift resistance of	at least

Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed **Opening Protection Level Chart Glazed Openings Openings** Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Garage Glass Entry Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate **Doors Block** Doors **Doors** Doors the weakest form of protection (lowest row) for Non-Glazed openings. Not Applicable-- there are no openings of this type on the structure X Α Verified cyclic pressure & large missile (9--Ib for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4--8 lb for windows doors/2 lb for skylights) c Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C Х No Windborne Debris Protection A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.) • SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials TEC Property Address_8801 WILES ROAD **CORAL SPRINGS**

33067

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter s	ystems with no documentation	on) All Glazed openings are protected with
protective coverings not meeting the requirements of An with no documentation of compliance (Level N in the tal		ms that appear to meet Answer "A" or "B"
N.1 All Non-Glazed openings classified as Level A, B, C, or	N in the table above, or no Non-O	Glazed openings exist
N.2 One or More Non-Glazed openings classified as Level I table above		
N.3 One or More Non-Glazed openings is classified as Leve	X in the table above	
X. None or Some Glazed Openings One or more Glaze	d openings classified and Leve	l X in the table above.
MITIGATION INSPECTIONS MUST B	E CERTIFIED BY A QUALIF	FIED INSPECTOR.
Section 627.711(2), Florida Statutes, provi	- ·	o may sign this form.
Qualified Inspector Name: THOMAS E. CHEEVER	License Type: PROFESSIONAL ENGINE	l .
Inspection Company: FLORIDA TECHNICAL, INC.		one: 3-765-0264
Qualified Inspector – I hold an active license as a	(check one)	
Home inspector licensed under Section 468.8314, Florida Statutes training approved by the Construction Industry Licensing Board a	-	
Building code inspector certified under Section 468.607, Florida	Statutes.	
General, building or residential contractor licensed under Section	489.111, Florida Statutes.	
Professional engineer licensed under Section 471.015, Florida Sta	tutes.	
Professional architect licensed under Section 481.213, Florida Sta	tutes.	
Any other individual or entity recognized by the insurer as posses verification form pursuant to Section 627.711(2), Florida Statutes	• • •	o properly complete a uniform mitigation
<u>Individuals other than licensed contractors licensed under Sunder Section 471.015, Florida Statues, must inspect the str</u>		-
Licensees under s.471.015 or s.489.111 may authorize a dire		
experience to conduct a mitigation verification inspection.		(1) This Ren Has Ren Electrosically Signed Thomas
I, THOMAS E. CHEEVER am a qualified inspector as (print name)	nd I personally performed th	e inspectio l'un August Squite Chercy, P.E. Printed Copies Of This Document Ar: Not Considered Signed And Scaled And The Signature What the Verified Co
contractors and professional engineers only) I had my employ	yee (perform See CASS 2022.08.3
	(print name of i	10 No.
and I agree to be responsible for his/her work.		No. 36054 ★ ★ O
Qualified Inspector Signature:	Date:	13:19:26
An individual or entity who knowingly or through gross neg		audulent mitigation verification of is
subject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (See		
certifies this form shall be directly liable for the misconduct		
performed the inspection.	or omproject as it the addition	ine and an analysis of the second sec
The second secon	T . 11 1 1	11.1
<u>Homeowner to complete</u> : I certify that the named Qualified residence identified on this form and that proof of identification		
Signature:I	Oate:	
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to wl of the first degree. (Section 627.711(7), Florida Statutes)	_	
The definitions on this form are for inspection purposes onl as offering protection from hurricanes.	y and cannot be used to certi	fy any product or construction feature
Inspectors Initials _TEC Property Address 8801 WILES R	OAD	CORAL SPRINGS 33067
*This verification form is valid for up to five (5) years provi	ded no material changes hav	e been made to the structure or

inaccuracies found on the form.

BUILDING 11 – ROOF PHOTOS











TEAR OFF OLD ROOF - 2013



DURING TEAR OFF - 2013



NEW TILE SET - 2013



TEAR OFF AND DRY IN - 2013




STRAP PHOTO - 2013



SWR AND DRY IN - 2013



SHEATHING NAILS - 2013



NAIL SPACING & SWR - 2013



TILE LOADED FOR INSTALL - 2013

_